

Aqua Enamel - Technical Data Sheet

Product Description

Supercoat™ Aqua Enamel is a highly durable Acrylic using high build long life protective coating technologies. Supercoat™ Aqua Enamel provides excellent coverage, is easy to apply and flows on with a brush, roller or can also be spray applied to create an abrasion resistant hard wearing polished surface. For use on primed wallboards, primed fibre and particle boards, wallpaper, timber and weatherboards.

Specifications

MSDS	010 - Version 1.0
Appearance	White to Mid Cream
Vehicle Type	Acrylic
Pigmentation	Titanium Dioxide
Solvent	Water
Finish	Gloss/Satin
Touch dry time	30 minutes at 20°C
Time to 2nd coat	2 hours at 20°C
Wet film thickness	50 microns
Solids Content	40.6 - 47.6%
Viscosity	95 - 105KU
Specific Gravity	1.18 - 1.4
Usual number of coats	2 - 3 (depending on substrate and colour density)
Toxicity	No added Chromites or Lead
Thinning & cleaning	Water
Coverage	8 - 12m ² /L depending on substrate profile and applicator
Pail type & size	Plastic 4L, 8L & 20L

Please Note

Do not apply at temperatures below 10°C or if it is likely to drop below 10°C during drying/curing time. Do not apply at temperatures over 30°C or if it is likely to go over 30°C during drying/curing time. Softens at temperatures over 70°C.

Manufacturer

Ironbark Technology Ltd
PO Box 2398, Dunedin, New Zealand.
Phone (03) 456 4222
info@ironbark.technology

The information contained herein is correct to the best of our knowledge. Due to product improvement and supply, these specifications may be subject to minor changes.