

## Ceramicoat Topcoat - Technical Data Sheet

### Product Description

A specially formulated highbuild matte coloured topcoat for Concrete Tiles. A water borne Acrylic polymer containing fungicides and light fast ceramic pigments for extended durability. Designed for maximum durability against Ultra Violet light, high humidity and erosion from strong winds and driving rain. The Supercoat™ Ceramicoat Topcoat is Alkali resistant. This product has been formulated to work as a barrier against moisture ingress whilst still allowing the building to breathe, allowing gaseous moisture to be expelled from inside the building.

### Specifications

<b>MSDS</b>	<b>014 - Version 1.0</b>
<b>Colour</b>	16 standard colours
<b>Vehicle Type</b>	Acrylic
<b>Solvent</b>	Water
<b>Touch dry time</b>	1 - 3 hours at 20°C
<b>Wet film thickness</b>	333 microns
<b>Solids Content</b>	40.6 - 47.6%
<b>Viscosity</b>	90 - 100KU
<b>Specific Gravity</b>	1.18 - 1.3
<b>Usual number of coats</b>	1 (depending on substrate profile and colour density)
<b>Toxicity</b>	No added Chromites or Lead
<b>Thinning &amp; cleaning</b>	Water
<b>Coverage</b>	2.5 - 3.0m <sup>2</sup> /L via airless spray (depending on substrate profile and applicator)
<b>Pail type &amp; size</b>	Plastic 20L

### Please Note

Do not apply at temperatures below 10°C or if it is likely to drop below 10°C during drying/curing time. Do not apply at temperatures over 30°C or if it is likely to go over 30°C during drying/curing time. Softens at temperatures over 70°C. Safe to use on surfaces that collect drinking water.

### Manufacturer

**Ironbark Technology Ltd**  
PO Box 2398, Dunedin, New Zealand.  
Phone (03) 456 4222  
info@ironbark.technology