



Surface Sealer - Technical Data Sheet

Product Description

Supercoat™ Surface Sealer is a fast drying multipurpose sealer particularly useful on concrete substrates including AAC, stucco roughcast plaster, block work, concrete, modified plasters, renders and timber.

Specifications

MSDS	006 - Version 1.0
Appearance	Milky Light Blue
Vehicle Type	Styrene Acrylic
Pigmentation	None
Solvent	Water
Finish	Clear Gloss
Touch dry time	25 minutes at 20°C
Time to 2nd coat	2 hours at 20°C
Dry film thickness	25 microns
Solids Content	26%
Viscosity	50 - 60 KU
Specific Gravity	1.03 - 1.4
Usual number of coats	1
Toxicity	No added Chromites or Lead
Thinning & cleaning	Water
Coverage	5-10m ² /L depending on substrate profile and applicator
Pail type & size	Plastic 8L & 20L

Please Note

Do not apply at temperatures below 10°C or if it is likely to drop below 10°C during drying/curing time. Do not apply at temperatures over 30°C or if it is likely to go over 30°C during drying/curing time. Softens at temperatures over 70°C.

Manufacturer

Ironbark Technology Ltd
PO Box 2398, Dunedin, New Zealand.
Phone (03) 456 4222
info@ironbark.technology

The information contained herein is correct to the best of our knowledge. Due to product improvement and supply, these specifications may be subject to minor changes.